



Flexible GNSS Receiver with Enhanced Connectivity Ideal for Base Station and Rover Applications

Benefits

Extra hardware not required
for sub-metre accuracy

Connectivity options
ease integration

Positioning enhanced with
increased signal availability

Excellent data security
and portability

Features

Robust, reliable RTK performance

Serial, Ethernet, USB and
Bluetooth[®] capable

Integrated support for OmniSTAR
and CDGPS

Removable Compact Flash

GPS+GLONASS

The DL-V3 features GPS-only or GPS+GLONASS functionality providing maximum flexibility and enhanced positioning in challenging environments. It supports the GPS L2C signal, and with a simple firmware upgrade, will be able to track the upcoming GPS L5 signal.

NovAtel's World-Class OEMV[®] Performance

NovAtel's OEMV-3 receiver drives the DL-V3's precision performance. For high-precision applications, NovAtel's RT-20[®] and RT-2[™] AdVance[™] RTK options provide real-time centimetre-level positions at a rate of up to 50 Hz. For sub-metre positioning, the DL-V3 enables L-band correction services such as OmniSTAR[®] or CDGPS.

Flexible Functionality and System Design

The DL-V3 provides numerous interfaces beyond the serial stand. *Bluetooth*[®] is available for close-in wireless connectivity, while Ethernet is available for remote network-based access to your receiver. Highly visible colored LEDs indicate receiver status at a glance. A removable Compact Flash card provides combined storage for up to two GB of logged data and the added convenience of data portability.

If you require more information about our enclosures,
visit novatel.com/products/enclosures.htm



novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)

or 403-295-4900

Europe 44-1993-85-24-36

SE Asia and Australia 61-400-833-601

Performance¹**Channel Configuration**

14 L1, 14 L2, 6 L5 GPS
12 L1, 12 L2 GLONASS
2 SBAS
1 L-band

Horizontal Position Accuracy (RMS)

Single Point L1	1.8 m
Single Point L1/L2	1.5 m
SBAS ²	0.6 m
CDGPS ²	0.6 m
DGPS	0.45 m
OmniSTAR ²	
VBS	0.7 m
XP	0.15 m
HP	0.1 m
RT-20 ³	0.2 m
RT-2	1 cm+1 ppm

Measurement Precision

L1 C/A Code	4 cm RMS
L1 Carrier Phase	0.50 mm RMS (differential channel)
L2 P(Y) Code	8 cm RMS
L2 Carrier Phase	1 mm RMS (differential channel)

Data Rate

Measurements	50 Hz
Position	50 Hz
OmniSTAR HP/XP	20 Hz

Time to First Fix (L1, L2)

Cold Start ⁴	60 s
Hot Start ⁵	35 s

Signal Reacquisition

L1	0.5 s (typical)
L2	1.0 s (typical)

Time Accuracy⁶ 20 ns RMS

Velocity Accuracy 0.03 m/s RMS

Velocity⁷ 515 m/s

Physical and Electrical

Dimensions 185 x 162 x 76 mm

Weight 1.3 kg

Power

Input Voltage +9 to +28 VDC
Power Consumption 3.5 W (typical)

Antenna Port Power Output

Output Voltage +5 VDC
Maximum Current 100 mA

Communication Ports

- 3 RS-232 serial ports or 2 RS-422 plus 1 RS-232 serial port
- 1 *Bluetooth* port
- 1 Ethernet capable port⁸
- 1 USB 1.1 port, USB device only

Input/Output Connectors

Power	4-pin LEMO
Antenna Input	TNC female
External Oscillator	BNC female
COM1	DB-9 male
COM2	DB-9 male
AUX	DB-9 male
I/O	DB-9 female
Ethernet	RJ-45
USB	Type B

Environmental

Temperature	
Operating	-40°C to +75°C
Storage	-50°C to +95°C
Humidity	95% non-condensing
Waterproof	IEC 60529 IPX7
Dust	IEC 60529 IP6X
Vibration (operating)	
Random	MIL-STD-810F, 514.5, Procedure1
Sinusoidal	IEC 68-2-6
Shock	IEC 68-2-27

**Compliance FCC, CE,
Industry Canada**

Included Accessories

- Automotive 12 VDC power cable
- Mounting bracket
- Serial cable
- Null-modem cable
- I/O interface cable
- Compact Flash

Optional Accessories

- GPS-700 series antennas
- ANT series antennas
- RF Cables—5, 10 and 30 m lengths
- AC adapters—International and North American

Additional Features

- Multiple software models, including L1 and L1/L2 GPS or GPS+ GLONASS and carrier phase positioning with RT-20 or RT-2 options
- Auxiliary strobe signals including a configurable PPS output and two mark inputs
- Supports RTCM SC-104 version 3.0, CMR version 3.0, CMR+, NMEA 0183 version 3.01, and RTCA DO-217 message types
- Field-upgradeable firmware

Additional Firmware Features

- RT-20
- ALIGN™
- GL1DE™
- OmniSTAR HP, XP, VBS, G2
- L5 signal tracking
- Pseudo Range/Delta-Phase (PDP) Positioning

Version 4 -Specifications subject to change without notice.

©2010 NovAtel Inc. All rights reserved.

NovAtel, RT-20 and OEMV are registered trademarks of NovAtel Inc. RT-2, GL1DE, ALIGN and AdvAnte are trademarks of NovAtel Inc. The *Bluetooth* word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by NovAtel Inc. is under license. Other trademarks and trade names are those of their respective owners. OmniStar is a registered trademark of OmniSTAR Inc.

Printed in Canada. D10677

DL-V3 February 2010

For the most recent details of this product:
novatel.com/Documents/Papers/DL-V3.pdf

¹ Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

² GPS only.

³ Expected accuracy after static convergence.

⁴ Typical value. No almanac or ephemerides and no approximate position or time.

⁵ Typical value. Almanac and recent ephemerides saved and approximate position and time entered.

⁶ Time accuracy does not include biases due to RF or antenna delay.

⁷ Export licensing restricts operation to a maximum of 18,288 meters and 515 meters per second.

⁸ The DL-V3 is user-configured for either Ethernet or Bluetooth, but not both simultaneously.

