

TE01 Specifications

| Circular Waveguides | | MIL-W-23068 Circular Waveguide | | |
|---------------------|----------------|--------------------------------|----------------|-----------|
| I.D. O.D (cm) | Frequency(GHz) | I.D. O.D (cm) | Frequency(GHz) | Type. |
| 3.810 x 4.445 | 11.6-16.0 | 3.810 x 4.318 | 11.6-16.0 | WRC530D14 |
| 3.213 x 3.493 | 13.2-18.9 | 3.254 x 3.660 | 13.6-18.7 | WRC621D14 |
| 2.809 x 3.175 | 15.9-21.9 | 2.779 x 3.109 | 15.9-21.9 | WRC727D14 |
| 2.416 x 2.858 | 18.6-25.6 | 2.383 x 2.713 | 18.6-25.6 | WRC849D14 |
| 1.742 x 2.413 | 25.3-34.9 | 2.024 x 2.278 | 21.9-30.1 | WRC997D14 |
| 1.748 x 2.256 | 25.3-34.9 | 1.748 x 2.002 | 25.3-34.9 | WRC116C14 |
| 1.610 x 1.905 | 27.3-38.8 | 1.509 x 1.712 | 29.3-40.4 | WRC134C14 |
| 1.384 x 1.588 | 32.4-44.0 | — | — | N/A |
| 1.267 x 1.588 | 34.8-48.0 | 1.270 x 1.473 | 34.8-48.0 | WRC159C14 |
| — | — | 1.113 x 1.316 | 39.8-54.8 | WRC182C14 |
| 0.940 x 1.270 | 46.4-63.9 | 0.953 x 1.105 | 46.4-63.9 | WRC212C14 |
| 0.897 x 1.113 | 50.0-68.0 | 0.833 x 0.986 | 53.1-73.1 | WRC243C14 |
| 0.739 x 0.953 | 62.0-84.0 | 0.714 x 0.866 | 61.9-85.0 | WRC283C14 |
| 0.632 x 0.795 | 69.7-95.9 | 0.635 x 0.737 | 69.7-95.9 | WRC318C14 |
| 0.511 x 0.737 | 86.0-115.0 | 0.556 x 0.658 | 79.6-110.0 | WRC364C14 |
| 0.472 x 0.635 | 93.0-128.0 | 0.478 x 0.579 | 92.9-128.0 | WRC424C14 |
| — | — | 0.437 x 0.538 | 101.0-139.0 | WRC463C14 |
| — | — | 0.358 x 0.460 | 124.0-171.0 | WRC566C14 |

日本総販売代理店



株式会社 アムテックス

〒156-0052

東京都世田谷区経堂5丁目20番16号