

CIRCULAR WAVEGUIDES				
Band	Frequency Range (GHz)		Circular Dia.(mm)	Flanges
K	Low	18-20.5GHz	11.557	54-001 UG-595/U
	Medium	20-24.5GHz	10.058	
	High	24-26.5GHz	8.331	
Ka	Low	26.5-33GHz	8.001	54-003 UG-599/U
	Medium	33-38.5GHz	6.350	
	High	38.5-40GHz	5.562	
Q(B)	Low	33-38.5GHz	6.350	67B-008 UG-383/U
	Medium	38.5-43GHz	5.562	
	High	43-50GHz	4.775	
U	Low	40-43GHz	5.334	67B-007 UG-383/U-M
	Medium	43-50GHz	4.775	
	High	50-60GHz	4.191	
V	Low	50-58GHz	4.191	67B-008 UG-385/U
	Medium	58-68GHz	3.581	
	High	68-75GHz	3.175	
E	Low	68-75GHz	3.454	67B-009 UG-387/U
	Medium	66-88GHz	3.175	
	High	88-90GHz	2.387	
W	Low	75-88GHz	2.844	67B-010 UG-387/U-M
	High	88-110GHz	2.387	
F	Low	90-115GHz	2.260	- UG-387/U-M
	High	115-140GHz	1.905	
D	Low	110-140GHz	1.854	- UG-387/U-M
	High	140-160GHz	1.498	

日本総販売代理店



株式会社 アムテックス

〒156-0052

東京都世田谷区経堂5丁目20番16号