

90° HYBRID

SURFACE MOUNT MODEL: DQS-30-450

FREQUENCY BANDWIDTH

30 - 450 MHz

FEATURES:

- ▶ Ultra-Wide Bandwidth (15:1)
- ▶ Small Package Size, Surface Mount
- ▶ Building Block For:
 - Power Amplifiers
 - Image Rejection Mixers
 - I & Q / SSB Modulators
 - Phase Shifters & More...




SPECIFICATIONS (Rev. D 06/26/25)

Frequency	30 - 450 MHz	
Insertion Loss (dB) *	Typ.	Max.
	1.2	1.7
Amplitude Unbalance (dB)	Typ.	Max.
	1	1.5
Phase Unbalance (Deg.)	Typ.	Max.
	$\pm 2^\circ$	$\pm 3^\circ$
Isolation (dB)	Typ.	Min.
	23	18
Power Rating	5 Watt (Max.)	
Impedance	50 Ohms (Nom.)	
VSWR	1.4:1 (Typ.)	
Operating Temperature Range	-40 to +85 °C	

* Insertion loss in excess of the theoretical 3 dB coupling.

Package # 102SLF



PORT IDENTIFICATION

Input	Isolated*	+90° Output	0° Output	GND
1	2	8	7	All Others

* Terminate isolated port in 50 Ohms externally.



90° HYBRID

SURFACE MOUNT MODEL: DQS-30-450

FREQUENCY BANDWIDTH

30 - 450 MHz

Data @ 25°C



PERFORMANCE PLOTS

90° HYBRID



SURFACE MOUNT MODEL: DQS-30-450

FREQUENCY BANDWIDTH

30 - 450 MHz

Data @ 25°C

PERFORMANCE PLOTS




90° HYBRID

SURFACE MOUNT MODEL: DQS-30-450

FREQUENCY BANDWIDTH

30 - 450 MHz

Data @ 25°C



PERFORMANCE PLOTS