ERZIA

DATASHEET

Band Pass Filter

ERZ-BPF-0350-0380-2.4

Main Features:

- Type: Band Pass Filter (BPF)
- Technology: Suspended Substrate
- Frequency range: 3.5 to 3.8 GHz
- Insertion Loss: 2.2 dB
- RF connectors (I/O): SMA Female
- Compact aluminum housing
- Hi-reliability and dedicated screening/ environmental tests available under request

ERZ-BPF-0350-0380-2.4

The ERZ-BPF-0350-0380-2.4 is a suspended substrate band pass filter integrated in a compact, rugged and connectorized module allowing easy integration in a wide range of final applications.

Typical applications:

- Industrial / Laboratory
- Satcom / Telecom
- Space / Aerospace / Military

Performance

Parameter	Value			Units
	Min	Typ	Max	
Frequency (passband)	3.5	-	3.8	GHz
Insertion Loss	-	2.2	2.5	dB
Return Loss	17	18	-	dB
Frequency for 30 dB out of band rejection	3.1	-	4.1	GHz
Frequency for 60 dB out of band rejection	2.9	-	4.3	GHz
CW Power Handling	-	-	10	W
RF Connectors	SMA Female IN/OUT			-

Insertion loss & Return loss

Figure 1 shows insertion loss and return loss measurements as a function of frequency at room temperature (25°C).



Figure 1: ERZ-BPF-0350-0380-2.4 Insertion & Return loss

Absolute Maximum Ratings

Condition	Value
Maximum Input Power (CW)	40 dBm
Operation temperature (at case)	-40 to 85 °C
Storage temperature	-55 to 125 °C

- Stress above these ratings may cause permanent damage to the device.
- It is final user responsibility to maintain the filter within the specified ranges.

ERZIA

DATASHEET

Band Pass Filter

ERZ-BPF-0350-0380-2.4

Mechanics and Housing



ERZIA TECHNOLOGIES S.L. OWNS THE COPYRIGHT OF THIS DOCUMENT WHICH SHALL NOT BE USED FOR ANY PURPOSED OTHER THAN THAT FOR WHICH IT IS SUPPLIED AND SHALL NOT BE COPIED OR GIVEN TO ANY PERSON WITHOUT WRITTEN AUTHORIZATION FROM ERZIA TECHNOLOGIES S.L.

ESTE DOCUMENTO ES PROPIEDAD DE ERZIA TECHNOLOGIES S.L. Y NO SERÁ VALIDO PARA NINGÚN OTRO FIN DIFERENTE DE AQUEL PARA EL QUE HA SIDO CREADO, NI SERÁ COPIADO NI ENTREGADO A TERCERAS PERSONAS SIN LA AUTORIZACIÓN EXPRESA DE ERZIA TECNOLOGIES S.L.

Measurements Conditions

All measurements provided in this report were performed at the following conditions:

Condition	Value
Temperature (DUT ON)	25 °C ± 1°C
Humidity	44% ± 10%
DUT Warm up time	30 min
DUT minimum operation time	24 hours
Test equipment warm up time	2 hours
Additional temperature cycles in climatic chamber (DUT OFF)	-40°C to 85°C

Environmental Specifications (By Design)

Operating Temperature:	-45 to +85 °C	(MIL-STD-810F, method 520.2)
Storage Temperature:	-55 to 125 °C	(MIL-STD-810F, method 520.2)
Vibration:	8g rms	(MIL-STD-810F, method 514.5)
Shock:	20g,11ms,saw-tooth	(MIL-STD-810F, method 516.5)
Acceleration:	15g	(MIL-STD-810F, method 513.5)

RoHS & REACH Compliance

This part is compliant with EU 2011/65/UE RoHS (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) and REACH (Registration, Evaluation, Authorization and restriction of Chemical substances) directives.

Documentation and Test Reports

All modules are at least delivered with: Electrical Test Report, Certificate of Conformance, Certificate of Acceptance and Origin. Optionally, units can be environmentally tested (temperature, vibration…).

Space / Military Usage

Most of ERZIA´s products are based on rad-hard technologies and can be manufactured and integrated according to MIL / ECSS or specific hi-rel standard-screening for space, aeronautics, military or specific hi-reliability usage.

Customization and Extended Performances

ERZIA can fully design or adapt one of the existing RF filters designs according to your specifications. Please contact us for additional information.

Model Number Codification



ERZIA

20210625_rev1.0

Copyright © 2021 ERZIA Technologies. All rights reserved. This information is commercial and indicative, subject to change without notice

Tel: +34 942 29 13 42 sales@erzia.com www.erzia.com