



GAJT-710MS

Enhanced single enclosure GPS Anti-Jam Technology (GAJT) for marine applications

Jamming and interference are constant threats

Jamming and interference, whether intentional or unintentional, can seriously degrade GNSS position, navigation and timing (PNT) availability—even to the point of total solution denial. Jammers create excessive noise, overpowering the low power GNSS signals and saturating the electronics in a GNSS receiver front end. Methods are needed to suppress this interference so your GNSS receiver continues to operate.

Enhanced functionality, same battle-proven small form factor

The GAJT-710MS is the next evolution of battle-proven anti-jam technology for marine platforms from Hexagon | NovAtel. It offers direction-finding functionality to support enhanced situational awareness and a new silent mode feature that reduces the thermal signature. It also has enhanced GNSS tracking performance. All these improvements are achieved while maintaining the same form and fit of the previous generation product.

How it works

GAJT-710MS mitigates interference by creating nulls in the antenna gain pattern in the direction of jammers, providing significant anti-jam protection even in dynamic multi-jammer scenarios. The output is a protected standard Radio Frequency (RF) signal, free from jamming and suitable for input to modern and legacy GNSS receivers.

Leading-edge technology

The commercial off-the-shelf (COTS) system uses NovAtel's seven element antenna array to receive GNSS signals in the L1 and L2 bands. Interference mitigation is achieved by applying proprietary digital null forming algorithms to the signals, creating dynamic nulls to give protection against narrowband and broadband interference sources. The unit is comprised of Radio Frequency (RF) front ends and null forming electronics. Integration to your GNSS receiver is seamless; DC power supply and data output are via separate connectors for which optional cables can be provided.

Protects GNSS navigation and precise timing receivers

GAJT-710MS protects GPS L1/L2, QZSS L1/L2, SBAS L1 and Galileo E1 signals. The wide bandwidth of the GAJT-710MS ensures future compatibility with M-Code GPS.



Benefits

- Commercial off-the-shelf (COTS)
- Low cost anti-jam protection for ships
 and boats
- Easy to integrate, ideal for retrofitting
- Anti-jam protection in dynamic multi-jammer scenarios
- Compatible with legacy and modern GNSS receivers, including M-Code
- Provides situational awareness
- Reduced thermal signature

Features

- Affordable protection for GNSS position, velocity and time
- 40 dB of interference suppression
- Single enclosure system
- Simultaneous GPS L1/L2, QZSS L1/L2, SBAS L1 and Galileo E1 protection
- Supports M-Code on GPS L1 & L2
- Adaptive digital nulling
- Jammer direction-finding
- Silent mode capability

Performance **GNSS** Signals L1 Band 1575.42 MHz ±12 MHz GPS L1, Galileo E1, QZSS L1, SBAS L1 L2 Band 1227.6 MHz ±12 MHz GPS L2, QZSS L2 **Interference Rejection** Simultaneous L1/E1 and L2 Interference suppression 40 dB (typical) Number of simultaneous nulling directions 6 Capabilities

- · Jammer direction-finding (Situational Awareness)
- · Silent mode (for reduced thermal signature)

Controlled Reception Pattern Antenna (CRPA)

Number of elements	7
Noise figure (typical)	3 dB
LNA gain	30 dB
VSWR	≤2.0:1
RF output	50 Ω TNC

Connectors

Power	MIL-C-26482, Series 2
RF	TNC (Female)
Data	MIL-DTL-38999, Series 3

Physical and Electrical

Dimensions

289 mm diametre x 120 mm height

Weight	7.5 kg
Power	
Power consumption	25 W
Input voltage	+10 to +33 VDC

Environmental Tomporaturo

Temperature		
MIL-STD-810G	(CH1), 501.6	
Operating	-40°C to +71°C	
Storage	-55°C to +85°C	
Humidity MIL-STD-810G(CH1), 507.6, Proc. II		
Altitude	MIL-STD-810G(CH1), 500.6	
Operating	3,600 m/12,000'	
Storage	12,000 m/40,000'	
Solar Radiatio	MIL-STD-810G(CH1), 505.6	
Corrosion	MIL-STD-810G(CH1), 509.6	
	MIL-STD-810G(CH1), 518.2	
	MIL-STD-810G(CH1), 504.2	
Water	MIL-STD-810G(CH1), 512.6	
	MIL-STD-810G(CH1), 506.6	
	IEC 60529 IPX6	
	IEC 60529 IPX7	
Sand and Dus	t MIL-STD-810G(CH1), 510.6	
	IEC 60529 IP6X	
Vibration	MIL-STD-810G(CH1), 514.7	
Shock	MIL-STD-810G(CH1), 516.7	
Drop	IEC 60068-2-31 Ec, Proc 1, 50 cm	
•		

Compliance

FCC, ISED, CE

Accessories

- 5 m unterminated GAJT-710 vehicle power cable (01018776)
- GAJT-710 data cable (01019845)

Export Approvals

Canadian Controlled Goods

- Single enclosure system for land and fixed applications
- 7-element antenna array

Other GAJT Products

· Easy to integrate, ideal for retrofitting

GAJT-410ML

GAJT-710ML



- Compact enclosure system for land and fixed applications
- 4-element antenna array · Direction-finding and jammer status
- Available in Olive Drab or Desert Tan
- Also available in white (GAJT-410MS)

GAJT-AE-N



- · Suitable for smaller platforms including UAVs
- · Antenna electronics for 4-element antenna arrays
- Works with most 4-element antenna arrays (supplied separately)
- Available as a card-only variant (GAJT-AE-R) for space constrained platforms.

4-Element Antenna Array

A 4-element antenna array allows gain pattern shapes to be changed in response to interference. Provides 3 independent nulls.



Contact Hexagon | NovAtel

sales.nov.ap@hexagon.com1-800-NOVATEL (U.S. and Canada) or 403-295-4900 | China: 0086-21-68882300 | Europe: 44-1993-848-736 | SE Asia and Australia: 61-400-883-601. For the most recent details of this product: novatel.com

GAJT and NovAtel are trademarks of NovAtel, Inc., entities within the Hexagon Autonomy & Positioning division, their affiliated entities, and/or their licensors. All other trademarks are properties of their respective owners.

©2021 NovAtel Inc. All rights reserved. NovAtel is part of Hexagon. NovAtel makes no representation or warranty regarding the accuracy of the information in this publication. This document gives only a general description of the product(s) or service(s) offered by NovAtel, and, except where expressly provided otherwise, shall not form part of any contract. Such information, the products and conditions of supply are subject to change without notice.