

Absorptive Digital Control Attenuator 0.1GHz-15GHz



Product Description

RFDAT0015G6R is an absorptive digital control attenuator with a frequency range of 0.1 to 15GHz.

The max power input is 23dBm. The insertion loss is 3.5dB with an attenuation range of 31.5dB.

The working temperature of this product is between - 40°C and + 85°C.

Features

- Absorptive Digital Control Attenuator
- Wide Band Operation 0.1-15GHz
- 0.5dB LSB Steps to 31.5dB

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications ($T_A = +25^\circ\text{C}$), $V_{dd} = +5\text{V}$, $V_{CTL} = 0 / +5\text{V}$

Parameter	Min	Typ	Max	Min	Typ	Max	Units
Frequency Range	0.1		5	5		15	GHz
Attenuation Range		31.5			31.5		dB
Attenuation Flatness: (Referenced to Insertion Loss)		± 2.0			± 2.0		dB
Control Bits			6			6	Bit
Control Step Size	0.5			0.5			dB
Insertion Loss		3.5	4.0		5.0	5.5	dB
Insertion Loss Temperature Coefficient		0.005			0.005		dB/ °C
Input VSWR (All States)		1.8	2.0		1.8	2.0	: 1
Output VSWR (All States)		1.8	2.0		1.8	2.0	: 1
Input 0.1 dB Compression Point (P0.1dB)		23			23		dBm
Input IP3		38			35		dBm
Switching Speed			800 Typ.				ns
Bias Current (+5V)			40 Max.				mA
Weight			0.044 Max.				lbs.
Impedance			50				Ohms
Input / Output Connectors	SMA-Female (Input) – SMA-Female (Output)						
Interface and Control Connector	MICRO-D9(Female)						
Package	Epoxy Sealed (Standard)						
	Hermetically Sealed (Optional)						

Absolute Maximum Ratings

Parameter	Rating
Biasing Voltage	+5V±10%
RF Input Power	+23dBm


Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-50°C to +105°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)


**For vibration testing details please see additional information section.

Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Insertion Loss @-40°C



Input VSWR @-40°C




Output VSWR @-40°C




Typical Performance Plots


Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Attenuation vs. Frequency



VSWR vs. Attenuation (S11)




VSWR vs. Attenuation (S22)




Typical Performance Plots


Attenuation Range Linearity




Attenuation Step Error Per Bit (dB)




Accumulated Attenuation Error (dB)




Relative Phase Shift



IIP3



Outline Drawing




Truth Table

TTL Control Voltage THRESHOLD						Low(0)=0~0.8V High(1)=2.8~5V
Control Input TTL						Attenuation State
C6	C5	C4	C3	C2	C1	Reference IL
0	0	0	0	0	0	0.5dB
0	0	0	0	1	0	1dB
0	0	0	1	0	0	2dB
0	0	1	0	0	0	4dB
0	1	0	0	0	0	8dB
1	0	0	0	0	0	16dB
1	1	1	1	1	1	31.5dB

Notes:

1. Package Material: Aluminum
2. Finish: Gold Plated
3. All dimensions are in millimeters [inches].
4. Housing Tolerances ± 0.1 [0.004] unless otherwise specified.
5. Standard torque wrench must be used to secure RF connectors.



Additional Information

Documentation

ESD Policy

https://rflambda.com/pdf/rflambda_esd_control.pdf

Connector Torque Specifications

https://www.rflambda.com/pdf/Torque_Specifications.pdf

Random Vibration Test Standard

https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Webpage

Ordering Information

Part Number	Modification	Description
RFDAT0015G6R	Standard	0.1GHz-15GHz Digital Control Attenuator

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.