




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFDAT0418G8H

Hermetically Sealed Absorptive Digital Control Attenuator 4 - 18GHz



Features

- Wide Band Operation 4-18GHz
- 0.25dB LSB Steps to 64dB
- Single Positive Control Line Per Bit
- Customization available upon request.

Typical Applications

- Wireless Infrastructure
- Military & Aerospace
- Test & Measurement

Electrical Specifications, $T_A = +25^\circ\text{C}$, $V_{dd} = +5\text{V}$, $V_{ss} = -5\text{V}$, $V_{CTL} = 0 / +5\text{V}$

Description	PN: RFDAT0418G8H						
	Absorptive Digital Attenuator						
Parameters	Min	Typ.	Max	Min	Typ.	Max	Units
Frequency Range	4-12			12-18			GHz
Attenuation Range			64			64	dB
Attenuation Flatness (Referenced to Insertion Loss)		± 1.0	± 3.0		± 3.0	± 6.0	dB
Control Bits	8						Bit
Control Step size		0.25			0.25		dB
Insertion Loss		5.5	7.0		7.0	8.0	dB
Insertion Loss Temperature Coefficient		0.01			0.01		dB/ $^\circ\text{C}$
Input VSWR (All Atten. States)		1.6	2.0		1.6	2.0	: 1
Output VSWR (All Atten. States)		1.6	2.0		1.6	2.0	: 1
Input 0.1 dB Compression Point ($P_{0.1\text{dB}}$)		25			25		dBm
Input IP_3		43			43		dBm
Weight	2.12						ounces
Impedance	50						Ω
Bias Current (+5V/-5V)	140 / 140						mA
Input / Output Connectors	SMA - Female						
Finish	Gold Plated						
Material	Aluminum						
Sealing	Hermetically Sealed (Laser Sealed)						

Hermetically Sealed Absorptive Digital Control Attenuator 4-18GHz



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFDAT0418G8H

Absolute Maximum Ratings

Biasing	+5V±10%/-5V±10%
TTL Control Voltage	0~0.8V/2~5V
RF Input Power	+27dBm

Ordering Information

Part No.	ECCN	Description
RFDAT0418G8H	EAR99	4-18GHz Digital Control Attenuator

Environmental Specifications and Test Standards

Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C
Storage Temperature		-55°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude		Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883	MIL-STD-883 (For Hermetically Sealed Units)

Hermetically Sealed Absorptive Digital Control Attenuator 4-18GHz




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS


RFDAT0418G8H

Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Insertion Loss @-45°C




Input VSWR @-45°C




Output VSWR @-45°C



Insertion Loss @+85°C



Input VSWR @+85°C



Hermetically Sealed Absorptive Digital Control Attenuator 4-18GHz




RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RFDAT0418G8H


Output VSWR @+85°C




Attenuation vs. Frequency




VSWR vs. Attenuation(S11)




VSWR vs. Attenuation(S22)




Attenuation Range Linearity




Attenuation Step Error Per Bit (dB)



Accumulated Attenuation Error(dB)



Relative Phase Shift



Hermetically Sealed Absorptive Digital Control Attenuator 4-18GHz




RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RFDAT0418G8H

Switching Speed



Switching Speed




Hermetically Sealed Absorptive Digital Control Attenuator 4-18GHz



Outline Drawing:

All Dimensions in mm [inches]



Truth Table

Control Voltage Input								Attenuation state
C8	C7	C6	C5	C4	C3	C2	C1	
1	1	1	1	1	1	1	1	Reference IL
1	1	1	1	1	1	1	0	0.25dB
1	1	1	1	1	1	0	1	0.5dB
1	1	1	1	1	0	1	1	1dB
1	1	1	1	0	1	1	1	2dB
1	1	1	0	1	1	1	1	4dB
1	1	0	1	1	1	1	1	8dB
1	0	1	1	1	1	1	1	16dB
0	1	1	1	1	1	1	1	32dB
0	0	0	0	0	0	0	0	64dB



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.