

WR34 Reflective Waveguide DPDT Electromechanical Switch 22GHz–33GHz



Product Description

RFDPDTW34A is a reflective waveguide DPDT electromechanical switch with a frequency range of 22 to 33GHz.

The power handling of this switch is 1KW max. The typical insertion loss is 0.15dB and the isolation is 60dB with the speed of 50ms. This electromechanical switch works with a +28 VDC power supply.

The electromechanical switch's interface is WR34.
The operating temperature of this product is from -40 to +70°C.

Features

- Reflective Waveguide Electromechanical Switch
- DPDT configuration
- Magnetic latching
- Operating life of 0.1 million cycles
- Guaranteed repeatability of 0.02dB up to 0.1 million cycle
- Standard Drive Compatible
- Supply Voltage +28VDC
- Insertion Loss +0.1dB
- Isolation 60dB

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25°C)

Parameter	Min	Typ	Max	Units
Frequency Range	22		33	GHz
Insertion Loss			0.1	dB
VSWR			1.1	:1
Isolation	60			dB
Average Power			500	W
Peak Power			1	KW
Switching Speed		50		ms
Life Cycles		0.1		Million
Repeatability			0.02	dB
Supply Current (V _{cc} = +28VDC)		1		A
Weight		0.64 Max.		lbs.
Impedance		50		Ohms
Waveguide Type		WR34		
Actuator Type		Latching		
Contact		Break Before Make		
Control		Ground		
Package		Epoxy Sealed (Standard)		
		Hermetically Sealed (Optional)		

Absolute Maximum Ratings


Parameter	Rating
Supply Voltage Range	+22 ~ +32VDC

Environmental Specifications and Test Standards


Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-50°C to +105°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
*Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight ≤20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

*For vibration testing details please see additional information section.

Control Methods




Control Port: Y50X-0807




Switch State	Pin 1	+28V Pin 2	Pin 3	Feedback Signal(Pin 5 is common)	
				Pin 4	Pin 5
State 1	Vcc	GND	OPEN	Connect with Pin 5	Disconnect from Pin 5
State 2	OPEN	GND	Vcc	Disconnect from Pin 5	Connect with Pin 5

Typical Performance Plots

VSWR



Outline Drawing



Notes:

1. Package Material: Aluminum
2. Inside Finish: Natural conductive oxidation; Outside Finish: Black paint with control part
3. All dimensions are in millimeters [inches].
4. Tolerances ± 0.02 [0.008] unless otherwise specified.



Additional Information

Documentation	Webpage
ESD Policy	https://rflambda.com/pdf/rflambda_esd_control.pdf
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFD PDTW34A	WR34	22GHz-33GHz Electromechanical Switch

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.