

50W Coaxial Mismatch Termination 0.01GHz-0.4GHz (5% BW)



Product Description

RFMNST50G04C is a narrow band mis-match load with a frequency range that can cover a 5% fractional BW between 0.01 and 0.4GHz.

This narrowband mismatch load can handle 50W CW and is available in a variety of VSWR options.

Features

- Wide frequency Band
- Low VSWR

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25°C)

Parameter	Min	Typ	Max	Units
Frequency Range *	0.01-0.4 (5% Fractional BW)			GHz
VSWR *	1.5,2,2.5,3,3.5,4,4.5,5,1.5±6.6% (Must select a value)			: 1
Average Power		50		W
Peak Power		10 (5μs pulse width with 0.5% duty cycle)		KW
Weight		1.33 Max.		lbs.
Impedance		50		Ω
Connector Type		N,SMA,BNC,TNC		
Connectors		Brass Nickel Plated		
Male Pin		Brass Gold Plated		
Female Pin		Beryllium Copper Gold Plated		
Package		Epoxy Sealed (Standard)		
		Hermetically Sealed (Optional)		


* Center Frequency and VSWR value must be selected when ordering

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-55°C to +125°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +125°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

**For vibration testing details please see additional information section.

Outline Drawing



Notes:

1. Package Material: Aluminum
2. Finish: Black Anodized
3. All dimensions are in millimeters [inches].
4. Standard torque wrench must be used to secure RF connectors.
5. Actual size may vary depending on the frequency and VSWR value chosen.



Additional Information

Documentation	Webpage
ESD Policy	https://rflambda.com/pdf/rflambda_esd_control.pdf
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFMNST50G04C	Standard	0.01GHz-0.4GHz Mismatch Termination

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.