

100W Coaxial Fixed Attenuator DC-12.4GHz



A



AB



C

Features

- Wide frequency Band
- Low VSWR
- Multiple Attenuation Values Available

Product Description

RFS100G12B is a coaxial fixed attenuator with a frequency range of DC to 12.4GHz.

The max average power of the attenuator is 100W. The max VSWR of 1.35:1.

The working temperature of this product is between - 40°C and + 85°C.

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25°C)

Parameter		Min	Typ	Max	Units
Frequency Range		DC		12.4	GHz
Attenuation Value & Accuracy	3		-1.0/+1.5		
	6		-1.0/+3.0		
	10		-2.0/+1.5		
	20		±1.5		dB
	30		±1.2		
	40		±1.2		
	50		±1.2		
VSWR				1.35	: 1
*Average Power				100	W
Peak Power (5μs pulse width with 10% duty cycle)				1	KW
Impedance			50		Ω
Weight	A		1.1 Max.		lbs.
	AB		3.14 Max.		lbs.
	C		3.97 Max.		lbs.
Connectors			N,SMA,TNC		


* Average Power: derated linearly to 10W @ 125°C.

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-55°C to +125°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +125°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight ≤20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)


**For vibration testing details please see additional information section.

Outline Drawing



Notes:

1. Housing: Aluminum
2. Finish: Black Anodize
3. All dimensions are in millimeters [inches].
4. Tolerances $\pm 3\%$ unless otherwise specified.



Additional Information

Documentation	Webpage
ESD Policy	https://rflambda.com/pdf/rflambda_esd_control.pdf
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFS100G12B	N,SMA,TNC	DC-12.4GHz Fixed Attenuator

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.