

Hermetically Sealed Reflective Coaxial SP3T Switch 0.6GHz-6GHz



Note: Photo is for illustration purposes only.
Please refer to outline drawing.

Features

- TTL compatible driver included
- Fast Switching Speed
- Single +12V Supply.
- High Power Cold Switching
- Insertion Loss 1.0dB Typical
- Isolation 65dB Typical
- 50 Ohm Matched

Product Description

RFSP3TR5M06GA-12VH is a hermetically sealed reflective coaxial single pole three throw switch with a frequency range of 0.6 to 6GHz.

The maximum power input of this switch is 100W CW. The insertion loss is 1.0dB with a typical isolation of 65dB.

The product features of fast switching speed, low insertion loss and high isolation.

The working temperature of this product is between - 40°C and + 85°C

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications(TA = +25°C), Vdd = +12V, TTL = 0 / +5V

Parameter		Min	Typ	Max	Min	Typ	Max	Units
Frequency Range			0.6 - 3			3 - 6		GHz
Insertion Loss			1.0			1.5		dB
Insertion Loss Temperature Coefficient			0.003			0.003		dB/ °C
Isolation		60			60			dB
Input VSWR			1.5			1.5		: 1
Output VSWR			1.5			1.5		: 1
RF Input Power (CW)				100			100	W
DC Power Dissipation			1.3			1.3		W
0.1dB Compression Point (P0.1dB)			50			50		dBm
IIP3			53			50		dBm
Switching Speed				400 Typ.				ns
Bias Current (+12V)				100 Typ.				mA
Weight	Net			/ Max.				lbs
	Including Heat sink			/ Max.				
Impedance				50				Ω
Input / Output Connectors		SMA-Female(Input) – SMA-Female(Output)						
Package	Epoxy Sealed (Standard)							
	Hermetically Sealed (Optional)							

Absolute Maximum Ratings

Parameter	Rating
Biasing	+12V±10%

Notes:


1. If the device operates in high power state, recommend keeping case temperature lower than 60°C.
2. Cold Switching: Before changing any TTL signal(s), the RF input power must be blanked or the switch could be damaged.

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-50°C to +105°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight ≤20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

** For vibration testing details please see additional information section.

Outline Drawing




Notes:

1. Package Material: Aluminum
2. Finish: Gold Plated
3. All dimensions are in millimeters [inches].
4. Housing Tolerances ± 0.1 [0.004] unless otherwise specified(Excl Heat Sink).
5. Heatsink Required - Mandatory for High Power Operation .Matching heatsink is listed on our website. If customer would like to use their own cooling method, please make sure the amplifier will operate under the specs that listed in page 2 of this datasheet.
6. Standard torque wrench must be used to secure RF connectors.

Truth Table

TTL Control Voltage THRESHOLD	Low(0)=0~0.8V High(1)=2.8~5V
-------------------------------	---------------------------------

Control Input TTL		Signal Path State
C1	C2	
0	0	J0-J1
0	1	J0-J2
1	0	J0-J2
1	1	ALL OFF
Control Pin Customization available upon request		



Additional Information

Documentation

Webpage

ESD Policy

https://rflambda.com/pdf/rflambda_esd_control.pdf

Heatsink Lookup Specifications

https://rflambda.com/search_heatsink.jsp

Connector Torque Specifications

https://www.rflambda.com/pdf/Torque_Specifications.pdf

Random Vibration Test Standard

https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFSP3TR5M06GA-12VH	Standard	0.6GHz-6GHz Hermetically Sealed SP3T PIN Diode Switch

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.