

Absorptive SP6T Electro-Mechanical Switch DC-110GHz



Note: Photo is for illustration purposes only.
Please refer to outline drawing.

Product Description

RFSP6T110EMC-T is an absorptive SP6T electro-mechanical switch with a frequency range of DC to 110GHz.

The typical insertion loss is 1.2dB and the isolation is 70 dB with a switching speed of 20ms. This electromechanical switch works with a +24 VDC power supply.

The working temperature of this product is between - 20°C and + 70°C

Features

- SP6T configuration
- Magnetic latching
- Operating life of 500 thousand cycles
- Guaranteed repeatability of 0.05dB up to 500 thousand cycles
- Excellent isolation, typically >60 dB to 90GHz
- Terminated ports
- TTL Drive
- Control Cable Included

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25°C)

Parameter		Min	Typ	Max	Units
Frequency Range			DC – 110		GHz
Insertion Loss	@DC-20GHz			0.6	dB
	@20-67GHz			1.2	dB
	@67-90GHz			1.5	dB
	@90-110GHz			1.8	dB
VSWR	@DC-20GHz			1.4	:1
	@20-67GHz			1.8	:1
	@67-90GHz			2.3	:1
	@90-110GHz			2.5	:1
Isolation	@DC-20GHz	80			dB
	@20-67GHz	70			dB
	@67-90GHz	60			dB
	@90-110GHz	60			dB
Input Power				1	W
Switching Speed				20	ms
Life Cycles		500,000			Times
Repeatability				0.08	dB
Supply Current (VCC=+24VDC)			0.2		A
Weight			0.44		lbs.
Impedance			50		Ohms
Connector			1.0mm-Female		
Actuator Type			Latching		
Contact			Break Before Make		
Control			TTL		
Package	Epoxy Sealed (Standard)				
	Hermetically Sealed (Optional)				

Absolute Maximum Ratings


Parameter	Rating
Supply Voltage Range	22 – 28VDC

Environmental Specifications and Test Standards


Parameter	Description
Operational Temperature	-20°C to +70°C (Case Temperature)
Storage Temperature	-50°C to +85°C
Thermal Shock	-20°C → +70°C (5 Cycles / 10 hours)
*Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +70°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

*For vibration testing details please see additional information section.

Functional Diagram



Control Port



Drive type

TTL Drive Voltage (High = 2.5 to 5.5V, Rated voltage: +3V, Low = 0 to 0.8V, Rated voltage: 0V)									
STATUS	Pin1	Pin 3	Pin 5	Pin 7	Pin 9	Pin 11	Pin13	Pin15	Pin16
RF to 1	VCC	High	Low	Low	Low	Low	Low	GND	Low
RF to 2	VCC	Low	High	Low	Low	Low	Low	GND	Low
RF to 3	VCC	Low	Low	High	Low	Low	Low	GND	Low
RF to 4	VCC	Low	Low	Low	High	Low	Low	GND	Low
RF to 5	VCC	Low	Low	Low	Low	High	Low	GND	Low
RF to 6	VCC	Low	Low	Low	Low	Low	High	GND	Low
Reset	VCC	Low	Low	Low	Low	Low	Low	GND	High


Note:

VCC: +22V ~ +28V (Rated voltage: +24V)

GND: Ground

Applying "High" to the corresponding pin can control the connection of the corresponding RF channel. At the same time, other RF channels are automatically disconnected and connected to the built-in 50 Ω load. When the High level "High" is applied to the "Reset" pin, all RF channels of the switch are disconnected and connected to the built-in 50 Ω load. Note that applying high to multiple pins at one time is forbidden and can damage the switch.

Outline Drawing



Notes:

1. Package Material: Aluminum
2. Finish: Gray Paint
3. All dimensions are in millimeters [inches].



Additional Information

Documentation

ESD Policy

https://rflambda.com/pdf/rflambda_esd_control.pdf

Connector Torque Specifications

https://www.rflambda.com/pdf/Torque_Specifications.pdf

Random Vibration Test Standard

https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFSP6T110EMC-T	Connectors 1.0mm-Female TTL	DC-110GHz SP6T Electromechanical Switch

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.