

SPDT Reflective Electro-Mechanical Switch DC-67GHz



Product Description

RFSPDT67EMB-T is a SPDT reflective electro-mechanical switch with a frequency range of DC to 67GHz.

The power of this switch is 1W Max. The typical insertion loss is 0.5dB and the Isolation is 70dB with the speed of 20ms.

This electromechanical switch works with typically +24 VDC power supply.

The working temperature of this product is between - 25°C and + 70°C

Features

- SPDT configuration TTL Control
- Magnetic latching
- Operating life of 1 million cycles
- Guaranteed repeatability of 0.05dB up to 1 million cycles
- Excellent isolation, typically >80 dB to 18GHz
- TTL/5V CMOS compatible.
- Control Cable Included

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25°C)

Parameter		Min	Typ	Max	Units
Frequency Range			DC – 67		GHz
Insertion Loss	@DC-10GHz		0.3	0.6	dB
	@10-20GHz		0.5	0.8	dB
	@20-67GHz		1.0	1.5	dB
VSWR	@DC-10GHz			1.28	:1
	@10-20GHz			1.5	:1
	@20-67GHz			2.02	:1
Isolation	@DC-10GHz	85			dB
	@10-20GHz	77			dB
	@20-67GHz	70			dB
Input Power				1	W
Switching Speed				20	ms
Life Cycles		1			Million
Repeatability				0.05	dB
Supply Current (VCC=+24VDC)			0.24	0.7	A
Weight			0.11 Typ.		lbs.
Impedance			50		Ohms
Connector			1.85mm-Female		
Actuator Type			Latching		
Contact			Break Before Make		
Control			TTL		
Package		Epoxy Sealed (Standard)			
		Hermetically Sealed (Optional)			

Absolute Maximum Ratings

Parameter	Rating
Supply Voltage Range	22 – 28VDC


Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-25°C to +70°C (Case Temperature)
Storage Temperature	-50°C to +85°C
Thermal Shock	-25°C → +70°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +70°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)


*For vibration testing details please see additional information section.

Typical Performance Plots


Insertion Loss@+25°C




Input VSWR@+25°C




Output VSWR@+25°C




Isolation@+25°C



Insertion Loss @-25°C




Input VSWR @-25°C




Typical Performance Plots


Output VSWR @-25°C




Isolation @-25°C




Insertion Loss @+70°C




Input VSWR @+70°C



Output VSWR @+70°C




Isolation @+70°C




Typical Performance Plots


Insertion Loss Temperature Coefficient




Insertion Loss vs. Temperature



Switching Speed



Switching Speed




Functional Diagram



Pin Descriptions

PIN 1 connect ground, PIN 2 connect +24V, PIN3 and PIN4 are control pins.




Parameter	PIN1	PIN2	PIN3	PIN4
Position A	GND	+24V	Open	TTL (3.3 to 5.0V)
Position B	GND	+24V	TTL (3.3 to 5.0V)	Open

Notes:

- Pin 1 must always be connected to ground.
- Before switching, microwave signal must not be present.

Outline Drawing



Notes:

1. Package Material: Aluminum
2. Finish: Black Paint
3. All dimensions are in millimeters [inches].
4. Housing Tolerances ± 0.5 [0.02] unless otherwise specified.



Additional Information

Documentation

ESD Policy

https://rflambda.com/pdf/rflambda_esd_control.pdf

Connector Torque Specifications

https://www.rflambda.com/pdf/Torque_Specifications.pdf

Random Vibration Test Standard

https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number

Modification

Description

RFSPDT67EMB-T

Connectors 1.85mm-Female TTL Control

DC-67GHz SPDT Electromechanical Switch

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.