

Reflective Coaxial SPST Switch 12GHz-18GHz



Note: Photo is for illustration purposes only.
Please refer to outline drawing.

Features

- TTL compatible driver included
- Fast Switching Speed
- Low Power Cold Switching
- Insertion Loss 2.2dB
- Isolation 65dB Typical
- 50 Ohm Matched

Product Description

RFSPSTR1218GP is a reflective coaxial single pole single throw switch with a frequency range of 12 to 18GHz.

The maximum power input of this switch is 30dBm. The insertion loss is 2.2dB with a typical isolation of 65dB.

The product features of fast switching speed, low insertion loss and high isolation.

The working temperature of this product is between - 40°C and + 85°C

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications(TA = +25°C), Vdd = +5V/-5V, TTL = 0 / +5V

Parameter	Min	Typ	Max	Units
Frequency Range		12~18		GHz
Insertion Loss		2.2		dB
Insertion Loss Temperature Coefficient		0.003		dB/ °C
Isolation (*J0→J1)		65		dB
Input VSWR		1.5		: 1
Output VSWR		1.5		: 1
RF Input Power			30	dBm
DC Power Dissipation		0.3		W
0.1dB Compression Point (P0.1dB)		20		dBm
IIP3		40		dBm
Switching Speed		100 Max.		ns
Bias Current (+5V / -5V)		80 / 50 Max.		mA
Weight		0.035 Max		lbs
Impedance		50		Ω
Input / Output Connectors	SMA-Female(Input) – SMA-Female(Output)			
Package	Epoxy Sealed (Standard)			
	Hermetically Sealed (Optional)			

* J0: Absorptive Port J1: Reflective port

Absolute Maximum Ratings

Parameter	Rating
Biasing	+5V±10%/-5V±10%


* TTL pins cannot be connected to the negative voltage otherwise the internal driver will be damaged.

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40 ⁰ C to +85 ⁰ C (Case Temperature)
Storage Temperature	-50 ⁰ C to +105 ⁰ C
Thermal Shock	-40 ⁰ C → +85 ⁰ C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85 ⁰ C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

** For vibration testing details please see additional information section.


Outline Drawing



Truth Table	
TTL Control Voltage	Low(0)=0~0.8V
THRESHOLD	High(1)=2.8~5V
Control Input TTL	State
0	ON
1	OFF
Control Pin Customization available upon request	

Notes:

1. Package Material: Aluminum
2. Finish: Gold Plated
3. All dimensions are in millimeters [inches].
4. Housing Tolerances ± 0.1 [0.004] unless otherwise specified.
5. Standard torque wrench must be used to secure RF connectors.



Additional Information

Documentation

Webpage

ESD Policy

https://rflambda.com/pdf/rflambda_esd_control.pdf

Connector Torque Specifications

https://www.rflambda.com/pdf/Torque_Specifications.pdf

Random Vibration Test Standard

https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFSPSTR1218GP	Standard	12GHz-18GHz SPST PIN Diode Switch

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.