

WR75 Waveguide Circulator 10.2GHz-11GHz



Note: Photo is for illustration purposes only.
Please refer to outline drawing.

Product Description

RFWC75C-10.3G11G is a waveguide circulator with a frequency range of 10.2 to 11GHz.

The circulator has a minimum isolation of 20dB. The maximum insertion loss is 0.25dB.

The circulator's interface is WR75.

Features

- High power handling up to 200W
- Wide band operation
- High isolation within operational band
- Low Insertion Loss

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications ($T_A=+25^{\circ}\text{C}$)


Parameter	Min.	Typ.	Max.	Units
Frequency Range	10.2		11.0	GHz
Insertion Loss			0.25	dB
Isolation	20			dB
VSWR			1.20	:1
Average Power (CW)			200	W
Peak Power			5	KW
Rotation		Clockwise (Standard) Counter Clockwise (upon request)		
Flange Type		Cover		
Waveguide type		WR75		

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-50°C to +125°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
*Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)


*For vibration testing details please see additional information section.

Typical Performance Plots



Mkr	Trace	X-Axis	Value	Notes
1 ▽	S21	10.600000 GHz	-0.1460 dB	
2 ▽	S11	10.600000 GHz	-27.9250 dB	
3 ▽	S12	10.600000 GHz	-27.8590 dB	
4 ▽	S22	10.600000 GHz	-27.4040 dB	
5 ▽	S33	10.600000 GHz	-26.8760 dB	

Outline Drawing



Notes:

1. Basis-material: Aluminum, Brass, Alloyed Cuprum, Stainless
2. External Body Finish: Body painted with gray/black epoxy enamel
3. Standard torque wrench must be used to secure RF connectors.
4. All dimensions are in millimeters [inches].

Additional Information

Documentation	Webpage
ESD Policy	https://rflambda.com/pdf/rflambda_esd_control.pdf
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFWC75C-10.3G11G	WR75	10.2GHz to 11GHz Waveguide Circulator

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.