

WR284 1500W High Power Waveguide Termination 2.6GHz-3.95GHz



Note: The photo is for illustration purposes only.
Please refer to the outline drawing.

Features

- Full band operation
- Low VSWR
- Rugged mechanical configuration

Product Description

RFWT284G is a waveguide high power termination with a frequency range of 2.6 to 3.95GHz.

The average power handling of this termination is 1500W.

The working temperature of this product is between -30°C and +70°C.

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications, TA = +25°C


Parameter	Min	Typ	Max	Units
Frequency Range	2.6		3.95	GHz
VSWR			1.25	: 1
Average Power (CW)		1500		W
Flange Type		UG1725/U, CPRF		
Waveguide Type		WR284		
Flange Holes		Through		

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-30°C to +70°C (Case Temperature)
Storage Temperature	-50°C to +125°C
Thermal Shock	-30°C → +70°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

**For vibration testing details please see additional information section.

Outline Drawing



Notes:

1. Material: Aluminum
2. Inside Finish: Chromate conversion; Outside Finish: Anticorrosion black paint.
3. All dimensions are in millimeters [inches].
4. The tolerance noted is just for reference.

Additional Information

Documentation

Connector Torque Specifications

Random Vibration Test Standard

Webpage

https://www.rflambda.com/pdf/Torque_Specifications.pdf

https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFWT284G	WR284	2.6GHz-3.95GHz High Power Termination

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.