

Manual / Programmable Attenuator 110dB Range 10dB Step DC-18GHz



Features

- High Power Handling Capability
- Low VSWR
- Excellent Temperature Stability
- Manual Control (Standard)
- Programmable upon request

Typical Applications

- Wireless Infrastructure
- Military & Aerospace
- Test and Measurement

Electrical Specifications, $T_A=25\text{ }^{\circ}\text{C}$

Parameters		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range		DC		8	DC		12.4	DC		18	GHz
Attenuation Range			110			110			110		dB
Attenuation Accuracy			± 4.5			± 4.5			± 4.5		dB
Attenuation Step			10			10			10		dB
VSWR				1.6			1.6			1.75	-
Insertion Loss		0.6+(0.09/GHz)									dB
Power Handling		1W (100W Peak with 10μS Pulse Width)									Watts
Operating Voltage *		24									V
Control Voltage *		3.3~5V (Pulse width 50mS~1S)									V
Control Current *		0.02-0.8									mA
Operating Current *		2									A
Switching Time *		20									ms
Repeatability		0.05									dB
Working Life		10 ⁶									Cycles
Weight	Manual	12.52									ounces
	Programmable	14.81									ounces
Connectors		SMA- Female									

* Note: These specifications apply to the programmable models

Manual / Programmable Attenuator 110dB Range 10dB Step DC-18GHz


Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-20°C~+70°C (Case Temperature)
Storage Temperature	-55°C~+85°C
Thermal Shock	-20°C → +75°C (5 Cycles / 10 hours)
Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)


Outline Drawing:

All Dimensions in mm

Manual Type



Programmable Type





Dimensions	A	B*	C	D	E	F
Programmable	114.4	8.3	44.3	6	103.6	135.8

B*: For N type units, this dimension is 28mm

Programmable Model Options (Manual Control is Standard)


Type A – Solder Connection Option



A

Type B – DSUB Connector Option

Programmable Attenuator



B

Programmable Version Individual Cell Attenuation Values

Value	Cell 1	Cell 2	Cell 3	Cell 4
11dB Range	10dB	40dB	20dB	40dB

Logic High (3.3V to 5V) activates the cell

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.