

300W Manual Control Attenuator 0.9GHz-4GHz (10% BW)



Product Description

RKT300G4A20 is a manual control attenuator with a frequency range of 0.9 to 4GHz.

The power handling of this attenuator is 300W. The attenuation range is 20dB.

The working temperature of this product is between - 10°C and +50°C.

Features

- Continuous variable attenuation during operation
- High power handling

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications, TA = +25°C

Parameter	Min	Typ	Max	Units
Frequency Range	0.9		4	GHz
Attenuation Range		20		dB
Attenuation Flatness		±0.15~±0.5		dB
Insertion Loss		0.5~1.0		dB
VSWR			1.5	: 1
Power (CW)		300 (2KW pulse with 330μs width)		W
Bandwidth		10		%
Weight		4.41 Max.		lbs
Impedance		50		Ohms


Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-10°C to +50°C (Case Temperature)
Storage Temperature	-40°C to +70°C
Thermal Shock	-10°C → +50°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +50°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)


*For vibration testing details please see additional information section.

Typical Performance Plots


Insertion Loss




Attenuation



Outline Drawing



Notes:
1. All dimensions are in millimeters [inches].



Additional Information

Documentation

Webpage

Connector Torque Specifications

https://www.rflambda.com/pdf/Torque_Specifications.pdf

Random Vibration Test Standard

https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RKT300G4A20	Standard	0.9GHz-4GHz Manual Control Attenuator

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.