




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RLNA21G24G

Low Noise Amplifier 21.7GHz~24.5GHz



Features

- Gain: 34dB Typical
- Noise Figure: 2.0dB Typical
- Output P1dB: +21dBm Typical
- Supply Voltage: +12V
- 50 Ohm Matched

Typical Applications

- Wireless Infrastructure
- RF Microwave & VSAT
- Military & Aerospace
- Test Instrument
- Fiber Optics

Electrical Specifications, TA = +25°C, Vcc = +12V

Parameter	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	21.7		23	23		24.5	GHz
Gain	32	34		32	34		dB
Gain Flatness		±0.5			±0.5		dB
Gain Variation Over Temperature (-45 ~ +85)		±1.0			±1.0		dB
Noise Figure		2.1	2.5		2.2	2.5	dB
Input VSWR		1.2	1.5		1.2	1.5	: 1
Output VSWR		1.5	1.8		1.5	1.8	: 1
Output 1dB Compression Point (P1dB)	19	21.5		19	21		dBm
Saturated Output Power (Psat)		22			22		dBm
Output Third Order Intercept (IP3)		26.5			26.5		dBm
Supply Current (Vcc=12V)		160	200		160	200	mA
Isolation S12		-55			-45		dB
Weight	3.53						Ounces
Impedance	50						Ohms
Input / Output Connectors	SMA-Female						
Finish	Standard: Gold 40 micron; Nickel 220 micron thickness						
	Option: Gold 80 micron; Nickel 180 micron thickness						
Material	Copper						
Package Sealing	Epoxy Sealing (Standard)						
	Hermetically Sealed (Optional)						

Low Noise Amplifier 21.7GHz~24.5GHz



Absolute Maximum Ratings

Operating Voltage	+15V
RF Input Power (RFIN)(Vcc= +12V)	-2dB m

Biasing Up Procedure


Step 1	Connect Ground Pin
Step 2	Connect input and output
Step 3	Connect +12V biasing
Power OFF Procedure	
Step 1	Turn off +12V biasing
Step 2	Remove RF connection
Step 3	Remove Ground.

Environmental Specifications


Operational Temperature (°C)	-45 to +85
Storage Temperature (°C)	-55 to +125
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35c, 95%RH at 40°c
Shock	20G for 11msec half sine wave, 3 axis both directions

Typical Performance Plots


Gain @+25°C




Input VSWR @+25°C



Output VSWR @+25°C



Isolation @+25°C






RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RLNA21G24G


Gain @-45°C




Input VSWR @-45°C




Output VSWR @-45°C




Isolation @-45°C




Gain @+85°C




Input VSWR @+85°C



Output VSWR @+85°C



Isolation @+85°C



Low Noise Amplifier 21.7GHz~24.5GHz




RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RLNA21G24G


Gain vs. Output Power




P1dB vs. Frequency



Output Third Order Intercept (IP3)



Noise Figure




Low Noise Amplifier 21.7GHz~24.5GHz



Outline Drawing:

All Dimensions in mm [inches]



Ordering Information

Part No.	ECCN	Description
RLNA21G24G	EAR99	21.7-24.5GHz Low Noise Amplifier

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Low Noise Amplifier 21.7GHz~24.5GHz