

WR12 Waveguide Directional Coupler 60.5GHz – 91.9GHz



Note: The photo is for illustration purposes only.
Please refer to the outline drawing.

Product Description

RWGCP12SC is a WR12 waveguide directional coupler with a frequency range of 60.5 to 91.9GHz.

The power of this directional coupler is 5W. The nominal coupling is 10dB with a minimal directivity of 30dB.

The working temperature of this product is between - 40°C and + 85°C.

Features

- High power handling up to 5W
- Full band operation
- Low VSWR
- Rugged mechanical configuration

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications, TA = +25°C


Parameter	Min	Typ	Max	Units
Frequency Range	60.5		91.9	GHz
Nominal Coupling		10		dB
Directivity	30			dB
VSWR Primary			1.15	: 1
VSWR Secondary			1.25	: 1
Power Handling (CW)		5		W
Waveguide Type		WR12		
Flange Type		UG387/U		
Package	Epoxy Sealed (Standard)			
	Hermetically Sealed (Optional)			

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-50°C to +105°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
*Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)


*For vibration testing details please see additional information section.

Outline Drawing



Notes:

1. Package Material: Copper/Brass
2. Finish: Gold Plated; Outside finish: Corrosion protected with grey paint.
3. All dimensions are in millimeters [inches].
4. Standard torque wrench must be used to secure RF connectors.
5. The tolerance noted is just for reference.



Additional Information

Documentation	Webpage
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RWGCP12SC	WR12	60.5GHz-91.9GHz Waveguide Directional Coupler

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.