




up to 6 GHz > 80 dB

Features:

- ◆ **Wireless Communication Test, EMI Test, Coupling Test, RF Function Test**
- ◆ **High quality, cost effective and fast delivery**
- ◆ **Customizable**

HJP - CD01		
	<p>Specification:</p> <p>Operation Mode: Manual</p> <p>Material: Aluminum</p> <p>Size: 160 x 220 x 75(mm)</p> <p>Ports: USB3.0 x 1, SMA - SMA x 2</p> <p>Options: Visual window x 1,</p> <p>Temperature Range: -10-50°C (14-122 °F)</p>	<p>Shielding Effectiveness</p> <p>Typical: ≥80dB@0.6 to 6 GHz</p> <p>Test Specification:92dB@0.6 to 1 GHz</p> <p>88dB@1 to 2 GHz</p> <p>85dB@2 to 4 GHz</p> <p>80dB@4 to 6 GHz</p>
HJP - CD03		
	<p>Specification:</p> <p>Operation Mode: Manual</p> <p>Material: Aluminum</p> <p>Size: 190 x 200 x 140(mm)</p> <p>Ports: USB3.0 x 2, 4 N - SMA x 4</p> <p>Temperature Range: -10-50°C (14-122 °F)</p>	<p>Shielding Effectiveness</p> <p>Typical: ≥80dB@0.6 to 6 GHz</p> <p>Test Specification:92dB@0.6 to 1 GHz</p> <p>88dB@1 to 2 GHz</p> <p>85dB@2 to 4 GHz</p> <p>80dB@4 to 6 GHz</p>
HJP - CD05		
	<p>Specification:</p> <p>Operation Mode: Manual</p> <p>Material: Aluminum</p> <p>Size: 250 x 300 x 170(mm)</p> <p>Ports: USB3.0 x 2, N - SMA x 4</p> <p>Temperature Range: -10-50°C (14-122 °F)</p>	<p>Shielding Effectiveness</p> <p>Typical: ≥80dB@0.6 to 6 GHz</p> <p>Test Specification:92dB@0.6 to 1 GHz</p> <p>88dB@1 to 2 GHz</p> <p>85dB@2 to 4 GHz</p> <p>80dB@4 to 6 GHz</p>

Shielding Boxes

HJP - CD07



Specification:

Operation Mode: Manual

Material: Aluminum

Size: 460 x 305 x 245(mm)

Ports: USB3.0 x 4, SMA - SMA x 4, N - N x 2

Options: AC power strip x 1

Temperature Range: -10-50°C (14-122 °F)

Shielding Effectiveness

Typical: ≥80dB@0.6 to 6 GHz

Test Specification:92dB@0.6 to 1 GHz

88dB@1 to 2 GHz

85dB@2 to 4 GHz

80dB@4 to 6 GHz

HJP - CD08



Specification:

Operation Mode: Manual

Material: Aluminum

Size: 457 x 305 x 240(mm)

Ports: USB3.0 x 4, SMA - SMA x 4, N - N x 2

Options: AC power strip x 1,

Visual window x 1, Glove x 2

Temperature Range: -10-50°C (14-122 °F)

Shielding Effectiveness

Typical: ≥80dB@0.6 to 6 GHz

Test Specification:92dB@0.6 to 1 GHz

88dB@1 to 2 GHz

85dB@2 to 4 GHz

80dB@4 to 6 GHz

HJP - CD10



Specification:

Operation Mode: Manual

Material: Aluminum

Size: 436 x 280 x 350(mm)

Ports: USB3.0 x 16, SMA - SMA x 2,

Options: Fan x 1

Temperature Range: -10-50°C (14-122 °F)

Shielding Effectiveness

Typical: ≥80dB@0.6 to 6 GHz

Test Specification:92dB@0.6 to 1 GHz

88dB@1 to 2 GHz

85dB@2 to 4 GHz

80dB@4 to 6 GHz

HJP - CD11		
	<p>Specification:</p> <p>Operation Mode: Manual</p> <p>Material: Aluminum</p> <p>Size: 435 x 300 x 345(mm)</p> <p>Ports: USB3.0 x 6, N - SMA x 12</p> <p>Temperature Range: -10-50°C (14-122 °F)</p>	<p>Shielding Effectiveness</p> <p>Typical: ≥80dB@0.6 to 6 GHz</p> <p>Test Specification:92dB@0.6 to 1 GHz</p> <p>88dB@1 to 2 GHz</p> <p>85dB@2 to 4 GHz</p> <p>80dB@4 to 6 GHz</p>
HJP - CD12		
	<p>Specification:</p> <p>Operation Mode: Manual</p> <p>Material: Aluminum</p> <p>Size: 436 x 220 x 350(mm)</p> <p>Ports: USB3.0 x 2, N - SMA x 4</p> <p>Options: AC power strip x 1, Visual window x 1,</p> <p>Temperature Range: -10-50°C (14-122 °F)</p>	<p>Shielding Effectiveness</p> <p>Typical: ≥80dB@0.6 to 6 GHz</p> <p>Test Specification:92dB@0.6 to 1 GHz</p> <p>88dB@1 to 2 GHz</p> <p>85dB@2 to 4 GHz</p> <p>80dB@4 to 6 GHz</p>
HJP - CD12B		
	<p>Specification:</p> <p>Operation Mode: Manual</p> <p>Material: Aluminum</p> <p>Size: 436 x 220 x 350(mm)</p> <p>Ports: USB3.0 x 4, N - SMA x 4</p> <p>Options: AC power strip x 1, Visual window x 1, diamond white ambient lighting</p> <p>Temperature Range: -10-50°C (14-122 °F)</p>	<p>Shielding Effectiveness</p> <p>Typical: ≥80dB@0.6 to 6 GHz</p> <p>Test Specification:92dB@0.6 to 1 GHz</p> <p>88dB@1 to 2 GHz</p> <p>85dB@2 to 4 GHz</p> <p>80dB@4 to 6 GHz</p>

Shielding Boxes

HJP - CD30



Specification:

Operation Mode: Manual

Material: Aluminum

Size: 436 x 280 x 350(mm)

Ports: USB3.0 x 4, N - SMA x 4,

USB charging port x 30

Options: AC power strip x 1, Visual window x 1, Fan x 2, Diamond white ambient lighting, Cellphone holder x 30

Temperature Range: -10-50°C (14-122 °F)

Shielding Effectiveness

Typical: ≥80dB@0.6 to 6 GHz

Test Specification:92dB@0.6 to 1 GHz

88dB@1 to 2 GHz

85dB@2 to 4 GHz

80dB@4 to 6 GHz

HJP - CD22



Specification:

Operation Mode: Manual

Material: Aluminum

Size: 800 x 600 x 2000(mm)

Ports: 64 USB, 16 N - SMA

Options: AC power strip x 8, Visual window x 1, Diamond white ambient lighting

Temperature Range: -10-50°C (14-122 °F)

Shielding Effectiveness

Typical: ≥80dB@0.6 to 6 GHz

Test Specification:92dB@0.6 to 1 GHz

88dB@1 to 2 GHz

85dB@2 to 4 GHz

80dB@4 to 6 GHz