

# SMART7

## Multi-frequency GNSS SMART antenna featuring powerful OEM7 technology



### Maximum performance

The OEM7 receiver and VEXXIS antenna inside the SMART7 allow it to receive GPS, GLONASS, BeiDou, Galileo and QZSS signals. Multiple GNSS signals deliver better satellite availability under variable terrain and environmental conditions. The SMART7 also receives L-Band signals providing easy access to the world-wide correction signals provided by TerraStar.

### ALIGN

ALIGN technology from Hexagon | NovAtel is optionally supported when combined with a second SMART7 or NovAtel receiver to provide relative heading and position that can be used to guide accessory vehicles. Wi-Fi can also be used to provide a wireless ALIGN solution to simplify communications in implement guiding applications.

### Terrain compensation for increased accuracy

With optional integrated terrain compensation, the SMART7 improves guidance and autosteer performance on uneven terrain and slopes by providing positions automatically corrected for vehicle pitch and roll.

### Maximum accuracy

The SMART7 can provide a range of performance accuracies from dual-frequency GLIDE to full centimeter-level RTK. TerraStar services provide decimeter or centimeter level accuracy using globally transmitted satellite corrections.

### Maximum connectivity

The SMART7 supports RS-232 and CAN bus communications. Optional 2.4 GHz Wi-Fi and 10/100 Ethernet connectivity allows connection to a vehicle's Wi-Fi network, routers, terminals or other SMART7 antennas. Wi-Fi and Ethernet connectivity can also be used to receive RTK or TerraStar corrections over NTRIP.

### Durable, field-ready design

This rugged SMART7 antenna is enclosed in a durable, waterproof housing that meets MIL-STD-810G environmental standards for many years of reliable use in the field. Magnetic and screw mounting is supported.

### Benefits

- Centimeter-level accuracy using TerraStar-C PRO, TerraStar-X and RTK
- 15 cm pass-to-pass accuracy using TerraStar-L
- High quality measurements and stable phase center for precision applications
- Terrain compensation corrects for vehicle roll and pitch to improve performance on uneven ground
- Simplified setup and configuration with optional onboard Setup & Monitor (Web) and wireless connectivity

### Features

- GPS, GLONASS, BeiDou, Galileo, QZSS plus TerraStar correction signal reception
- Simultaneously track up to 3 TerraStar Correction Service satellites
- Optional heading and relative positioning using ALIGN
- Integrated NTRIP client using optional Ethernet/Wi-Fi interface
- Advanced ISOBUS-compatible CAN interface supports NMEA2000, NovAtel messages and firmware updates

**Performance<sup>1</sup>****Signal Tracking**

GPS	L1, L2, L2C, L5
GLONASS	L1, L2
Galileo	E1, E5a/b, E5 AltBOC
BeiDou	B1I, B1C, B2I, B2a, B2b
QZSS	L1, L2
SBAS	L1
L-Band	

**Horizontal Position Accuracy****(RMS)**

Single point L1/L2	1.2 m
SBAS <sup>2</sup>	60 cm
DGPS	40 cm
TerraStar-L <sup>3,4</sup>	40 cm
TerraStar-C PRO <sup>3,4</sup>	2.5 cm
TerraStar-X <sup>3,4</sup>	2.0 cm
RTK	1 cm + 1 ppm

**(95%)**

Single point L1/L2	2.4 m
SBAS <sup>2</sup>	120 cm
DGPS	80 cm
TerraStar-L <sup>3,4</sup>	50 cm
TerraStar-C PRO <sup>3,4</sup>	3 cm
TerraStar-X <sup>3,4</sup>	2.5 cm
RTK	2.5 cm + 1 ppm

**Pass-to-Pass Accuracy (95%)**

L1/L2 GLIDE Single Point	35 cm
TerraStar-L	15 cm
TerraStar-C PRO	2 cm

**Maximum Data Rate**

Measurements	Up to 20 Hz
Position	Up to 20 Hz

**Time to First Fix**

Cold start <sup>5</sup>	<40 s (typical)
Hot start <sup>6</sup>	<20 s (typical)

**Signal Reacquisition**

L1	0.5 s (typical)
L2	<1.0 s (typical)

**Velocity Accuracy<sup>7</sup>**

0.03 m/s RMS

**Time Accuracy<sup>9</sup>**

20 ns RMS

**Terrain Compensation Accuracy<sup>9</sup>**

Roll/Pitch 0.5 degrees RMS

**Physical And Electrical****Dimensions**

220 L x 192 W x 66 H mm

**Weight**

&lt;1.1 kg

**Connectors**14-pin Tyco Ampseal  
Optional M12 D-Coded**Mounting**4 x M4 screw inserts  
Integrated magnetic mount**Power**Input voltage range +7 to +30 VDC  
Power consumption<sup>10</sup> 4 W (typical)**Status LEDs**

Multi-colored, daylight viewable

**Communication Ports**

RS-232 dedicated ports	3
CAN Bus	1
1 PPS	1
Ground speed output	1
Wi-Fi	Optional
Ethernet	Optional

**Environmental****Temperature**

Operating	-40°C to +70°C
Storage	-45°C to +80°C

**Humidity**

MIL-STD-810G Method 507.6

**Immersion**

MIL-STD-810G Method 512.6

**Shock**

MIL-STD-810G Method 516.7

**Solar Radiation**EN60950-22 8.2  
ISO 9022-9, Method 20,  
Severity Degree 03**Salt Fog**

IEC 60068-2-11

**Sand and Dust**

MIL-STD-810G Method 510.5

**Vibration Random**

MIL-STD-810G, Method 514.7

**Ingress Protection Rating** IP67**Compliance**FCC, ISED, CE, E-Mark and  
Global Type Approvals**Standard Features**

- 20 Hz data rates
- Field upgradable software
- PAC multipath mitigating technology
- Differential correction support for RTCM 2.1, 2.3, 3.0, 3.1, CMR, CMR+ and RTCA
- Navigation output support for NMEA 0183 and detailed NovAtel ASCII and binary logs
- GLIDE smoothing algorithm
- 1 PPS output
- Ground speed output

**Correction Services**

- TerraStar-L
- TerraStar-C PRO
- TerraStar-X
- RTK ASSIST
- RTK ASSIST PRO

**Available Hardware Options**

- SMART7
- SMART7-W with Wi-Fi
- SMART7-I with Wi-Fi and Ethernet

**Firmware Solutions**

- GLONASS tracking
- Galileo tracking
- BeiDou tracking
- L-Band tracking
- ALIGN
- RTK
- Terrain Compensation

**Optional Accessories**

- Mounting plate
- Interface cable
- RELAY7

1. Typical values (open sky conditions). Performance specifications subject to GNSS system characteristics, Signal-in-Space (SIS) operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources. 2. GPS only. 3. Requires subscription to TerraStar data service. Subscriptions available from NovAtel. 4. RMS/95% accuracy under ideal conditions and may vary based upon user's geographic region, ionospheric activity, scintillation levels, GNSS availability and constellation health, multipath conditions and presence of interference sources. 5. Typical value. No almanac or ephemerides and no approximate position or time. 6. Typical value. Almanac and recent ephemerides saved and approximate position and time entered. 7. Export licensing restricts operation to a maximum of 515 meters per second. 8. Time accuracy does not include biases due to RF or antenna delay. 9. With Terrain Compensation software model installed, requires firmware version 7.06.01 or later. 10. Power consumption values for GPS L1/L2.

## Contact Hexagon | NovAtel

sales.nov.ap@hexagon.com 1-800-NOVATEL (U.S. and Canada) or 403-295-4900 | China: 0086-21-68882300 | Europe: 44-1993-848-736 | SE Asia and Australia: 61-400-883-601.  
For the most recent details of this product: novatel.com

ALIGN, GLIDE, NovAtel, OEM7, RTK ASSIST, TerraStar and VEXXIS are trademarks of NovAtel, Inc., entities within the Hexagon Autonomy & Positioning division, their affiliated entities, and/or their licensors. All other trademarks are properties of their respective owners.

©2021 NovAtel Inc. All rights reserved. NovAtel is part of Hexagon. NovAtel makes no representation or warranty regarding the accuracy of the information in this publication. This document gives only a general description of the product(s) or service(s) offered by NovAtel, and, except where expressly provided otherwise, shall not form part of any contract. Such information, the products and conditions of supply are subject to change without notice.