

LB-OH-112-10-C-3.5F Octave Horn Antenna 6-12GHz 10dB Gain 3.5mm Female

Octave Horn Antenna Operating From 6GHz to 12GHz With a Nominal 10dB Gain With 3.5mm Female Connector

Product Information

SKU	LB-OH-112-10-C-3.5F
-----	---------------------

Description

Octave horn antenna LB-OH-112-10-C-3.5F, operating from 6 to 12GHz with a nominal 10dB gain and low VSWR 1.5:1 with 3.5mm Female output connector. The model LB-OH-112-10-C-3.5F has uniform gain through its frequency span, providing efficient performance characteristics and directionality. It can handle 50W continuously and 100W peak power. Constructed of lightweight corrosion-resistant aluminum, the antenna will provide years of trouble-free indoor and outdoor service. This octave horn antenna is linearly polarized and ideally suited for EMI testing, direction finding, surveillance, antenna gain and pattern measurements and other applications.

Technical Specification


Electrical Specification		Interface	
Frequency, Min (GHz)	6	Output Type	Coaxial
Frequency, Max (GHz)	12	Connector	3.5mm
Gain, Typ (dBi)	10	Connector Gender	Female
Polarization	Linear	Mechanical Specification	
3dB Beamwidth, E-Plane, Min (Deg.)	29	Body Material	Al
3dB Beamwidth, E-Plane, Max (Deg.)	76	Finish	Chemical Conversion Coating, Gray Paint
3dB Beamwidth, H-Plane, Min (Deg.)	29	Size, W (mm)	52
3dB Beamwidth, H-Plane, Max (Deg.)	61	Size, H (mm)	47.8
Cross Pol. Isolation, Typ (dB)	35	Size, L (mm)	130
VSWR, Typ	1.5:1	Weight, (kg)	0.135
Impedance, (Ohm)	50		
Power Handling, CW, (W)	50		
Power Handling, Peak, (W)	100		

Additional Information


Application	General Purpose Indoor & Outdoor, Fixed	Solution for	Gain Reference Antenna Measurement Far-field Measurement System Intergration
-------------	---	--------------	--

Outline Drawing

3.5mm-Female Output (P/N: LB-OH-112-10-C-3.5F)




3.5mm-Female Output with Round Mounting Bracket (Option, P/N: LB-112-10-C-MB)




3.5mm-Female Output with L Type Mounting Bracket (Option, P/N: LB-112-10-C-MBL)

Typical Test Results

Gain




Antenna Factor




Antenna Factor (Table)

Frequency(GHz)	Gain(dBi)	AF(dB/m)
6.0	8.35	37.42
6.5	9.82	36.65
7.0	10.28	36.84
7.5	10.60	37.11
8.0	11.05	37.22
8.5	11.86	36.94
9.0	12.43	36.87
9.5	12.60	37.16
10.0	13.17	37.04
10.5	14.04	36.59
11.0	13.53	37.50
11.5	13.79	37.63
12.0	14.79	37.00


Cross Polarization Isolation




VSWR








Beamwidth



Pattern







Related Products



LB-112-10-C-MB Round Type Mounting Bracket



LB-112-10-C-MBL L type mounting bracket



Tripod_15Kg Al Alloy Tripod



3033HL Wooden Tripod



3033QM Wooden Tripod
Metalfree

Similar Products




LB-OH-112-10-C-NF Octave Horn
Antenna 6-12GHz 10dB Gain N
Type Female



LB-OH-112-10-C-NFSPO Octave
Horn Antenna 6-12GHz 10dB
Gain N Type Female




LB-OH-112-10-C-SF Octave Horn
Antenna 6-12GHz 10dB Gain
SMA Female



LB-OH-112-10-C-SFSPO Octave
Horn Antenna 6-12GHz 10dB
Gain SMA Female



LB-OH-112-10-C-TF Octave Horn
Antenna 6-12GHz 10dB Gain TNC
Female




LB-OH-112-10-C-TFSPO Octave
Horn Antenna 6-12GHz 10dB
Gain TNC Female



LB-OH-112-10-C-7 Octave Horn
Antenna 6-12GHz 10dB Gain
7mm



LB-OH-112-10-C-7SPO Octave
Horn Antenna 6-12GHz 10dB
Gain 7mm



LB-OH-112-10-C-3.5F SPO Octave
Horn Antenna 6-12GHz 10dB
Gain 3.5mm Female

About this Datasheet

<ul style="list-style-type: none">● Product Information <p>Product Link: https://www.ainfoinc.com/lb-oh-112-10-c-3-5f-octave-horn-antenna-6-12-ghz-10db-gain-3-5mm-female Data subject to change without notice. © A-INFO INC. 2024. All Rights Reserved</p>	<ul style="list-style-type: none">● Contact Us <p>Address: 60 Tesla, Irvine, CA 92618, USA</p> <p>Website: www.ainfoinc.com</p> <p>Email: sales@ainfoinc.com</p>	<ul style="list-style-type: none">● Phone & Fax <p>Phone: +1-949-639-9688 +1-949-639-9608</p> <p>Fax: +1-949-639-9670</p>
--	---	--