


UNAUTHORIZED USE OF THIS  
DRAWING IS STRICTLY PROHIBITED

DAR	REV	DESCRIPTION	APPVD	DATE
4770	A	INITIAL RELEASE	DG	2-14
10157	B	SEE DAR	DG	7-25



PORT CONFIGURATION				
INPUT	J1	J2	J3	J4
J1	---	ISOLATION	-3dB<0 DEG	-3dB<-90 DEG
J2	ISOLATION	---	-3dB<-90 DEG	-3dB<0 DEG
J3	-3dB<0 DEG	-3dB<-90 DEG	---	ISOLATION
J4	-3dB<-90 DEG	-3dB<0 DEG	ISOLATION	---

- NOTES:**
- LEAD MATERIAL: 99.99% PURE SILVER  
.005 [1.27] THICK.
  - SEE 90° APPLICATION NOTE FOR FURTHER INFORMATION.
  - RoHS COMPLIANT.
  - DATA AND SPECIFICATIONS APPLY WHEN PART IS MOUNTED IN IPP TEST FIXTURE. TEST FIXTURE CONFIGURATION/FOOTPRINT AVAILABLE ON REQUEST.

**ELECTRICAL SPECIFICATIONS**

FREQUENCY:	1000 - 3000 MHz.
INSERTION LOSS:	< 0.25 dB
VSWR:	< 1.35:1
ISOLATION:	> 16 dB
AMPLITUDE BALANCE:	±1.1 dB
PHASE BALANCE:	±5°
POWER:	450 WATT
TEMPERATURE:	-55°C TO 85°C

MATERIAL AL. ALLOY, 6061-T6	DWN S.Cornell	DATE 8-20-13	<b>Innovative Power® Products</b>		
	ENG DG	DATE 8-13			
FINISH CHEM FILM CLEAR PER MIL-DTL-5541, TYPE 2, REV F, CLASS 3 ROHS COMPLIANT	MANUF	DATE	TITLE OUTLINE, COUP., 90°, 1000 - 3000 MHz. 450W		
	CAGE CODE: 437R2		SIZE B	P/N IPP-2307	REV. B
TOLERANCE IN [MM]	.XX ±.02 [.50] .XXX ±.010 [.254] ANG. ±1/2°	SHEET OF 1 1	SCALE 4:1		